





SPECIFICATIONS



















915Vn 19" TFT MONITOR

Line / Size	Value 19"
Visible screen size (cm)	48
Screen format	4:3
Panel Type TFT Active Matrix LCD, Slim Cabir	net, X/-/X / X
Diagonal Hard Coating (3H), Anti-glare Treatment	
Brightness (cd/m²)	300
Contrast ratio	2000:1 (DCR)
Pixel / Dot Pitch (mm)	0.294 x 0.294
Display area (mm)	376,3 x 301
Viewing angle (H/V)	CR>=10 170/160
Response Time (typ) tr + tf	5 ms
Compatibility	
VESA, XGA, VGA, SVGA	SXGA
WXGA	-
Mac®Equipped With VGA Port	X
Scanning Frequency	
Horizontal / Vertical	H:31.5~80KHz,V:55~75Hz
Pixel Frequency	135 MHz
Resolutions	
Maximum Resolution	1280 x 1024@75Hz
Recommended Resolution	1280 x 1024@60Hz
Resolution Supported	640x480@60/72/75Hz;
	720x400@70Hz;
	800x600@60/75Hz;
	832x624@74Hz;
	1024x768@60/70/75Hz;
	1280x1024@60/75Hz
Colours	16.7 M
Signal Input	
Analogue Input: D-Sub	X
Digital Input: DVI-D / HDMI	X/-
Connectors	
D-Sub 15 pin	X
DVI-D 24-pin:	X
HDMI	-
Power	
Power Source	Universal 110~240VAC,
	50/60Hz
Power Consumption	on<= 36W, Standby < 1W
EPA ENERGY STAR ®	Yes
Other Features	
Plug & Play	DDC2B, DCC CI
User Control	AUTO, Menu, Power, Eco/Up, Down
Function	Brightness, Contrast, Eco Mode, Gamma
	(1,2,3); DCR; Focus; Clock, H/V Position,
	Color Temp., Color Boost, Picture Boost,
2001	OSD Setup, Auto Config, Reset, Information
OSD Languages	9 Languages
Speaker	2 x 1W
Regulations (CUL, FCC, CE, Vista premium, GOST, RoHS, Pixel Fault, Class
Emissions Standard	TC0 03
Other Featureas	Tilt ,VESA 100 mm Wall Mountable, Kensington Security Slot, Protection Glass
Dimensions	
W x H x D with base (mm)	Monitor: 417.8 x 417.3 x 57.8
	Net: 5.5 kg /
weignt	- '
Weight	Gross: 7 kg
	Gross: 7 kg 40" 2125 pcs / 20" 1020 pcs
Loading Qty w/pallet Warranty	Gross: 7 kg 40" 2125 pcs / 20" 1020 pcs 3 Years Parts & Labour